

1 Stationary QR code scanner with RS232 HD-S63



The HD-S63 QR and barcode reader is a device designed for stationary use. Its small size allows for efficient use of workspace. **The scanner is made of high-quality materials and has an IP54 rating, meaning it is resistant to external factors such as dust and moisture. An RS232 cable is included.**

Stationary QR code scanner with RS232 HD-S63

Model	HD-S63-RS232	Device dimensions	10,6x7,3x14,3 cm
Matrix	640*480 CMOS	Package dimensions	18x16,8x12,1 cm
Scanning method	automatically (after presenting the code)	Device weight	370 g
Scan confirmation	sound and light signal	Weight in packaging	528 g
Compatible with the operating system	Linux, Android, Windows XP, 7, 8, 10, MacOS	Operating temperature	0 - 60°C
Interface	RS232	Storage temperature	-20 - 60°C
Cable length	170 cm	Working humidity	5 - 95%
Degree of protection	IP54	Storage humidity	5 - 95%
1D codes read	EAN-8, EAN-13, EAN-13 5, ISBN, UPC-A, UPC-E, Code 39, Code 39 FullASCII, Code 93, Code 128, Codabar, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, GS1-128, GS1 DataBar (RSS14) (Stacked), GS1 DataBar Limited, Standard 25, GS1 DataBar Expanded	2D codes read	PDF417, MicroPDF417, MicroQR, Data Matrix, QR Code

