



**The HD340 wired code reader** is the perfect solution for built-in applications. The device supports scanning 1D and 2D codes, achieving a speed of up to 200 scans per second. The availability of settings modifications allows you to configure the prefix or suffix.

<b>Model</b>	HD340	<b>Scanning speed</b>	<b>200 scans/second</b>
<b>Material</b>	ABS+TP	<b>Scanning method</b>	automatically
<b>Light source</b>	LED	<b>Scan confirmation</b>	Beep
<b>Matrix</b>	CMOS	<b>Scan angle</b>	360 degrees
<b>Resolution</b>	644x488	<b>Power</b>	5V
<b>Colour</b>	black	<b>Drop resistance</b>	up to 1.6 meters
<b>Material</b>	ABS	<b>Interface</b>	USB/RS232
<b>Weight of the device</b>	80 g	<b>Weight with packaging</b>	170 g
<b>Device dimensions</b>	8 x 6.8 x 5.3 cm	<b>Dimension</b>	17 x 9 x 6 cm
<b>Readable 1D codes</b>	EAN-13, EAN-8, UPC-A, UPC-E, CODE 128, CODE 39, CODE 93, CodaBar, Interleaved 2 of 5, Industrial 25, Matrix 2 of 5, CODE 11, MSI Plessey, RSS-14, RSS-Limited, RSS-Expanded		
<b>Readable 2D codes</b>	QR, DataMatrix, PDF417, Micro QR, HanXin		