

Industrial QR WIFI scanner with station HD4600-LR



The HD4600-LR industrial scanner is a robust and rugged device with IP67 protection, designed for scanning 1D and 2D barcodes, including QR, DataMatrix. It offers two types of wireless connection: 2.4G and Bluetooth. The reader will work well both in the store, in the warehouse and in production.

Industrial QR WIFI scanner with station HD4600-LR

Model	HD4600-LR	Charging time	4-6 hours
Matrix type	CMOS	Interface	USB
Resolution	1280 x 1024	Cable length	1,2 m
Scanning method	manually (on a button)	Protection degree	IP67
Scan confirmation	light signal, sound signal and vibration	Resistance to falls	up to 7 meters
Reading distance	up to 7 meters	Operating temperature	0°C-50°C
Scan angle	34° vertical, 40° horizontal	Storage temperature	-40°C-70°C
WIFI communication	2.4G, Bluetooth	Operating humidity	50% - 95%
Wireless range	100 m for 2.4G, 10 m for Bluetooth	Docking station dimensions	16,5 x 11 x 8,5 cm
Print contrast	≥30%	Product dimensions	10 x 7 x 17 cm
Operating voltage	(3.3V~4.2V) ±5%	Package dimensions	20 x 16 x 12 cm
Maximum current	480 mA	Product weight	200 g
Battery capacity	2600 mAh	Weight with packaging	500 g
Readable 1D codes	Code128, UCC/EAN-128, AIM128, EAN-8, EAN-13, ISBN/ISSN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-4 Matrix 2 of 5, Industrial 25, Standard 25, Code39, Codabar Code 93, Code 11 itp.		
Readable 2D codes	PDF417, QR Code (QR1/2, Micro), Data Matrix (ECC200, ECC000, 050, 080, 100, 140), Chinese Sensible Code itp.		

