

Stationary 1D and 2D industrial scanner HD650



The HD650 industrial scanner is designed for incredibly fast fast of 1D and 2D barcodes, including QR. This makes it successful for use on production lines. The device offers an **RS232 interface**, which makes it possible to **connect it under various programs to automate production processes.**

Stationary 1D and 2D industrial scanner HD650

Model	HD650-RS232	Operating current	300 mA (typical), 450 mA (max)
Fabrication material	aluminum housing	Standby current	100 mA \pm 5%
Scanning method	automatically	Protection degree	IP65
Scan confirmation	Light and sound signal	Operating temperature	-20°C - 50°C
Resolution	1280 x 800 px	Storage temperature	-40°C - 70°C
Scan angle	horizontally 46°, vertically 29°	Product dimensions	3,6 x 4,3 x 2,4 cm
Print contrast	>20%	Product weight	75 g
Interface	RS232	Package dimensions	19 x 10 x 7,2 cm
Power supply	5-36 VDC	Product weight	100 g
Readable 1D codes	UPCA, UPCE, EAN 8, EAN 13, Code 128, Code 39, Code 93, Code 32, Code 11 Codabar, Plessey, MSI, Interleaved 2 of 5, IATA 2 of 5, Matrix 2 of 5, Straight 2 of 5, Pharmacode, RSS-14, RSS-14 Expanded, RSS-14 Limited, Composite, Code-A, Composite Code-B, Composite Code-C		
Readable 2D codes	PDF417, Micro PDF 417, Data Matrix, OR, Micro QR, MaxiCode		

