

## Thermal transfer label printer OPrint-DA200N



The OPrint-DA200N is a compact label and barcode printer that offers thermal or thermal transfer printing at speeds up to 203 mm/sec and 203 dpi resolution. Equipped with a LAN interface, push-button controls and LED indicators, it will prove useful in office, warehouse and retail applications.

<b>Model</b>	OPrint-DA200N	<b>Roll type</b>	continuous paper, die-cut, black mark paper, fan-fold, linerless thermal label
<b>Material</b>	ABS plastic	<b>Roll width</b>	20~118 mm
<b>Printing method</b>	thermal and thermal transfer	<b>Roll thickness</b>	0.06~0.254 mm
<b>Resolution</b>	203 dpi	<b>Shaft diameter</b>	25.4 mm
<b>Maximum print speed</b>	203 mm/s	<b>Label roll capacity</b>	127 mm (5")
<b>Maximum print width</b>	104 mm	<b>Label length</b>	5~25,400 mm
<b>Maximum print length</b>	25,400 mm	<b>Device dimensions</b>	19 x 19,8 x 28 cm
<b>CPU</b>	400MHZ, 32-bit, ARM9	<b>Package dimensions</b>	39,5 x 25,5 x 24 cm
<b>RAM</b>	128MB SDRAM	<b>Weight of device</b>	2,8 kg
<b>Operating voltage</b>	AC 100-240V, 2.5A, 50-60Hz	<b>Weight with packaging</b>	3,2 kg
<b>Interface</b>	USB 2.0, USB Host 2.0, RS-232, Ethernet	<b>Operating temperature</b>	5 - 40°C
<b>Buttons</b>	switch, feed button	<b>Storage temperature</b>	-40 - 60°C
<b>Printer command languages</b>	EPL, ZPL, ZPL II, DPL, TSPL	<b>Operating humidity</b>	25% - 85%
<b>Ribbon length</b>	maximum 300 m	<b>Storage humidity</b>	10% - 90%
<b>Ribbon width</b>	30 mm ~ 110 mm		
<b>Printed 1D codes</b>	Code 11, Code 39, Code 93, Code 128, UPC-A, UPC-E, UCC-128, Codebar, EAN/JAN-8, EAN/JAN-13, Interleaved 2 of 5, ITF14, MSI Pleassy, PostCode, Telepen		
<b>Printed 2D codes</b>	QR CODE, PDF 417, Micro QR Code, Micro PDF417, Grid Matrix, MaxiCode, Aztec Code, Data Matrix		
<b>Certificates</b>	FCC Class A, CE Class A, CCC, BIS, CB		