



# Thermal Label Printer OPrint-XD200N

<b>Model</b>	OPrint-XD200N	<b>Driver</b>	Windows/Linux/Mac
<b>Resolution</b>	203 dpi	<b>SDK</b>	Windows/ Android/ iOS
<b>Printing method</b>	thermal printing	<b>Processor</b>	32-bit processor
<b>Max. printing speed</b>	152 mm (6") / s	<b>Memory</b>	8 MB Flash memory, 8 MB SDRAM, Flash memory is expandable up to a max of 4 GB
<b>Max. print width</b>	108 mm (4.25")	<b>Operating voltage</b>	AC 110-240V
<b>Max. print length</b>	1778 mm	<b>Dimensions of the device</b>	21,5 x 17,8 x 15,5 cm
<b>Media type</b>	continuous, intermittent, black mark, folded and punched	<b>Dimensions of the package</b>	21 x 29 x 19 cm
<b>Media width</b>	26 mm ~ 116 mm	<b>Weight of the device</b>	1,3 kg
<b>Media thickness</b>	0,06 ~ 0,254 mm (2,36 ~ 10 miles)	<b>Weight with packaging</b>	2,1 kg
<b>Media core diameter</b>	25,4 ~ 76,2 mm (1 „~ 3 ")	<b>Working temperature</b>	5 ~ 40°C
<b>Label length</b>	10 mm ~ 1778 mm	<b>Storage temperature</b>	-40 ~ 60°C
<b>Print head life</b>	50 km	<b>Working humidity</b>	25 ~ 85% non-condensing
<b>Sensors</b>	Slot sensor; Cover open sensor; Black mark sensor	<b>Storage humidity</b>	10 ~ 90% non-condensing
<b>Rotation</b>	0°, 90°, 180°, 270°	<b>1D barcode</b>	Code 39, Code 93, Code 128UCC, Code 128 podzbiory A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN i UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11
<b>Interface</b>	USB+Lan	<b>2D barcode</b>	PDF-417, Maxicode, DataMatrix, QR, Aztec
<b>Printer command language</b>	TSPL, EPL, ZPL, DPL		

