

# Standalone access controller SecureEntry-AC900HF



**SecureEntry-AC900HF is a standalone access controller.** Offers authentication by **RFID card and individual password.** It is equipped with **Wiegand 26 interface,** which gives the possibility to connect with external devices. It **features DC12V and operates at 13.56 MHz.**

# Standalone access controller SecureEntry-AC900HF

<b>Model</b>	SecureEntry-AC900HF	<b>Operating voltage</b>	DC 12V $\pm$ 12%
<b>Reading distance</b>	2-10 cm	<b>Operating current</b>	1,2A
<b>Device type</b>	standalone access controller	<b>Interlock relay</b>	DC 12V/3A
<b>Verification type</b>	RFID card, password	<b>Operating temperature</b>	40% - 90%
<b>Operation frequency</b>	13,56 mHz	<b>Operating humidity</b>	18,5 x 13,9 x 5,5 cm
<b>Max. number of employees in the base</b>	1000	<b>Product dimensions</b>	12,3 x 8,4 x 2,3 cm
<b>Keyboard and keys</b>	touch	<b>Package dimensions</b>	18,5 x 13,9 x 5,5 cm
<b>Readable chip types</b>	Mifare	<b>Product weight</b>	200 g
<b>Interface</b>	Wiegand 26	<b>Weight with packaging</b>	400 g

