

# RFID reader with access control SecureEntry-CR60HF



**SecureEntry-CR60HF is an RFID card reader offering control and management of access to buildings and premises. It supports 13,56 MHz cards. Features compact shape and elegant design. It offers a DC voltage of 9-16V and has a Wiegand 26 interface with the ability to change to Wiegand 34.**

# RFID reader with access control SecureEntry-CR60HF

<b>Model</b>	SecureEntry-CR60HF	<b>Data transfer</b>	in real time
<b>Warranty</b>	1 year	<b>Operating voltage</b>	DC 9V - 16V, standard 12V
<b>Device type</b>	RFID reader with access control	<b>Operating current</b>	70mA
<b>Frequency of operation</b>	13,56 MHz	<b>Interface</b>	Wiegand 26 or 34-60°C
<b>Verification type</b>	RFID card	<b>Operating temperature</b>	-25°C - 75°C
<b>Speed of response</b>	less than 0.2 seconds	<b>Operating humidity</b>	10%-90%
<b>Reading distance</b>	2-10 cm, dependent on card or tag	<b>Product dimensions</b>	8,6 x 8,6 x 8,2 cm
<b>Light signal</b>	two-color LED	<b>Package dimensions</b>	10,5 x 9,6 x 3 cm
<b>Sound signal</b>	built-in speaker (buzzer)	<b>Product weight</b>	100 g
<b>Kontrola dostępu</b>	tak	<b>Weight with packaging</b>	250 g
<b>Communication distance</b>	100 meters		

