

1

## Reliable HD-SL62 barcode reader



**The HD-SL62 corded code reader is made of high-quality materials and has a robust design, making it shock and drop resistant. It offers fast and efficient reading of leading one-dimensional codes.**

## The reliable HD-SL62 barcode scanner

Model	HD-SL62		
Building material	ABS + PC	Degree of protection	IP54
Light source	650 nm diode laser	Scanning speed	50 times/second
Sampling pattern	Single scan	Scanning the depth of field	0 - 350mm ( 0,33 mm pcs0.9 )
Scanning process	by hand	Lifting angle	65°
Tension	5V	Deflection angle	55°
Power consumption	85 mA (Spitzenstrom: 120)	Print contrast	30 UPC / EAN 100
Interface	USB	Operating temperature	0 do 45°C
Weight of the device	153 g	Storage temperature	od -20 do 60°C
Weight with packaging	313 g	Humidity during operation	5 to 85% relative humidity, non-condensing
Dimensions of the device	70 x 170 x 90 mm	Daylight	5000 Lux
Packaging dimensions	100 x 80 x 240 mm	Length of the cable	200 cm
Read 1D codes	EAN - 8 , EAN-13 , UPC- A, UPC- E , Code 39, Code 128 , EAN128		

