

The HD580 wired code scanner is an automatic device that automatically starts up when motion is detected and then scans the code.

The equipment is great for both standard barcodes and 2D multidimensional codes.

HD580 wired automatic code reader

| Model | HD580 | Weight of the reader | 120 g |
|--------------------------|---|----------------------------|-------------------|
| Light source | 617nm CMOS LED | Weight with packaging | 250 g |
| Scanning method | manual / automatic | Dimensions of the device | 165 x 85 x 70 mm |
| Confirmation of scanning | light and sound | Dimensions of the receiver | 20x15x6mm |
| Interface | USB, Virtual COM-USB | Package dimensions | 165 x 100 x 80 mm |
| Cable length | 170 cm | Operating temperature | -20∼50°C |
| Working time | up to 45 hours | Storage temperature | -40∼70℃ |
| Charging time | up to 4 hours | | |
| Readable 1D codes | UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Standard 2 of 5, Coda bar, MSI Plessey, GS1, China Post, Databar(RSS), Korea, NEC2 of 5, | | |
| Readable 2D codes | QR Code, Data Matrix, PDF417, Aztec, Maxicode | | |



